

**3M** Science.  
Applied to Life.™

 **Beta Bank**

 **Beta Bank**

**0%**

**0%**

**Strong adhesive.  
Strong value.**

3M™ Scotchcal™ Graphic Film with Comply™ Adhesive IJ35C  
3M™ Scotchcal™ Graphic Film IJ35

This calendared graphic film adheres strongly to flat, smooth surfaces making it reliable for the long haul. Affordably priced, it also boasts maximized reception of ink for color dense prints and Comply™ air release technology for easier installation. Create eye-catching applications for indoor and outdoor promotional graphics, signs, trade shows, POP displays and more.

See what's possible at [3M.com/IJ35C](http://3M.com/IJ35C)

# No lifting. No peeling. No worries.

With 3M™ Scotchcal™ Graphic Film IJ35 and 3M™ Scotchcal™ Graphic Film with Comply™ Adhesive IJ35C, you can find value that sticks.

- ▶ Permanent, pressure-sensitive adhesive
- ▶ Maximized ink reception for color-dense prints
- ▶ Use on smooth, flat and simple curved surfaces
- ▶ Most common substrates include rigid plastic, painted surfaces and metal
- ▶ Features 3M™ Comply™ air release technology for easier installation
- ▶ Available in gloss and matte finishes
- ▶ Up to 5-year expected performance life
- ▶ Recommended graphic protection includes 3M™ Scotchcal™ Gloss Overlaminates 8508, 3M™ Scotchcal™ Luster Overlaminates 8509 and 3M™ Scotchcal™ Matte Overlaminates 8510.

Learn more at [3M.com/IJ35C](https://www.3m.com/IJ35C)



Commercial Solutions  
3M Center, Bldg 220-12E-04  
St. Paul, MN 55144 USA  
1-800-328-3908  
[3M.com/Graphics](https://www.3m.com/Graphics)

**Warranty and Limited Liability.** The following is made in lieu of all other express or implied warranties, including any implied warranty of merchantability or fitness for a particular purpose. All 3M products are warranted to be free of defects in materials and manufacture at the time of shipment and to meet the specifications stated in the film or media's Product Bulletin. Also see 3M Graphics Warranties Bulletin, which gives the terms, additional limitations of the warranty, if any, and limitations of liability. For warranty information, visit [3M.com/GraphicsWarranties](https://www.3m.com/GraphicsWarranties).



## Typical properties

Details	
Adhesive Color	Gray
Adhesive Features	Pressure-sensitive
Adhesive Type	Solvent Acrylic
Application	Displays, Labeling
Application Surface	Simple Curve, Flat with Rivets, Flat
Color Palette	White
Converting Process	Inkjet Printing
Factory ISO Certification	No ISO Certification information available
Film Thickness (Imperial)	3.15 mil
Film Thickness (Metric)	80 Micron
Film Type	Vinyl
Imaging Method	Digital Print, Latex Inkjet, UV Inkjet, Solvent Inkjet
Maximum Service Temperature (Celsius)	90 °C
Maximum Service Temperature (Fahrenheit)	194 °F
Minimum Service Temperature (Celsius)	-50 °C
Minimum Service Temperature (Fahrenheit)	-58 °F
Opacity	Opaque
Product Code	IJ35-20,IJ35-10
Product Color	White
Product Usage	Opaque Signs, Buildings, Displays, Walls
Removability	Not Removable
Service Life	5 Year
Substrate	Paint, PMMA, Glass, Polycarbonate, ABS, Aluminum
Surface Finish	Glossy, Matte